

Package: latex2exp (via r-universe)

October 15, 2026

Type Package

Title Use LaTeX Expressions in Plots

Version 0.9.8

Date 2024-07-05

Description Parses and converts LaTeX math formulas to R's plotmath expressions, used to enter mathematical formulas and symbols to be rendered as text, axis labels, etc. throughout R's plotting system.

License MIT + file LICENSE

URL <https://www.stefanom.io/latex2exp/>,
<https://github.com/stefano-meschiari/latex2exp>

BugReports <https://github.com/stefano-meschiari/latex2exp/issues>

Encoding UTF-8

Suggests tools, testthat, waldo, knitr, ggplot2, rmarkdown, purrr,
tibble, reactable, htmltools, RCurl, rlang, dplyr

VignetteBuilder knitr

RoxygenNote 7.2.3

Language en-US

Repository <https://stefano-meschiari.r-universe.dev>

Date/Publication 2024-08-16 17:48:53 UTC

RemoteUrl <https://github.com/stefano-meschiari/latex2exp>

RemoteRef HEAD

RemoteSha 733d5d28f76058ff849f137d7c2d58133ac303e9

Contents

latex2exp	2
latex2exp_examples	2
latex2exp_supported	3

plot.expression	3
print.latexpexpression	4
print.latextoken2	4
render_latex	5
TeX	5
Index	7

latex2exp	<i>Deprecated; use TeX instead.</i>
-----------	---

Description

Deprecated; use [TeX](#) instead.

Usage

```
latex2exp(string, output = c("expression", "character", "ast"))
```

Arguments

string	A character vector containing LaTeX expressions. Note that any backslashes must be escaped (e.g. "\$\alpha\$").
output	The returned object, one of "expression" (default, returns a plotmath expression ready for plotting), "character" (returns the expression as a string), and "ast" (returns the tree used to generate the expression).

Value

Returns an expression (see the output parameter).

latex2exp_examples	<i>latex2exp Examples</i>
--------------------	---------------------------

Description

Plots a number of example LaTeX string, as parsed by [TeX](#).

Usage

```
latex2exp_examples(cex = 1)
```

Arguments

cex	Multiplier for font size
-----	--------------------------

latex2exp_supported	Returns the list of supported LaTeX commands.
---------------------	---

Description

If show is TRUE, also show a searchable table of symbols.

Usage

```
latex2exp_supported(show = FALSE, ...)
```

Arguments

show	Show a searchable table of symbols
...	Other parameters (not used)

Value

A data frame containing a table of supported LaTeX commands.

plot.expression	Previews a LaTeX equation
-----------------	---------------------------

Description

Plots the result of a call to [TeX] on the current graphical device. This is useful to preview the output before placing it on a plot.

Usage

```
## S3 method for class 'expression'
plot(x, ..., main = NULL)
```

Arguments

x	A plotmath expression returned by TeX .
...	Parameters to be passed to the text function.
main	Title of the plot

Examples

```
plot(TeX("Example equation: $a \\geq b$"))
```

```
print.latexexpression
```

Print an expression returned by TeX()

Description

Prints out the plotmath expression generated by TeX and the original TeX string.

Usage

```
## S3 method for class 'latexexpression'
print(x, ...)
```

Arguments

x	Object to print
...	Ignored

```
print.latextoken2
```

Prints out a parsed LaTeX object, as returned by TeX(..., output = 'ast'). This is primarily used for debugging.

Description

Prints out a parsed LaTeX object, as returned by TeX(..., output = 'ast'). This is primarily used for debugging.

Usage

```
## S3 method for class 'latextoken2'
print(x, depth = 0, ...)
```

Arguments

x	The object
depth	Increases padding when recursing down the parsed structure
...	(Ignored)

render_latex	<i>Renders a LaTeX tree</i>
--------------	-----------------------------

Description

Returns a string that is a valid plotmath expression, given a LaTeX tree returned by parse_latex.

Usage

```
render_latex(tokens, user_defined = list(), hack_parentheses = FALSE)
```

Arguments

tokens	tree of tokens
user_defined	any custom definitions of commands passed to TeX
hack_parentheses	render parentheses using group('(', phantom(), ' . ') and group(')', phantom(), ' . '). This is useful to return valid expressions when the LaTeX source contains mismatched parentheses, but makes the returned expression much less tidy.

Value

String that should be parseable as a valid plotmath expression

TeX	<i>Converts LaTeX to a plotmath expression.</i>
-----	---

Description

TeX converts a string comprising LaTeX commands (such as a math equation) to a [plotmath](#) expression. Plotmath expressions can be used through R's graphic system to represent formatted text and equations.

Usage

```
TeX(
  input,
  bold = FALSE,
  italic = FALSE,
  user_defined = list(),
  output = c("expression", "character", "ast")
)
```

Arguments

<code>input</code>	A character vector containing LaTeX strings. Note that any backslashes must be escaped (e.g. <code>"\$\\alpha"</code>).
<code>bold</code>	Whether to make the entire label bold
<code>italic</code>	Whether to make the entire label italic
<code>user_defined</code>	Described in the "Adding New Commands" section.
<code>output</code>	The returned object, one of "expression" (default, returns a plotmath expression ready for plotting), "character" (returns the expression as a string), and "ast" (returns the tree used to generate the expression).

Value

Returns a plotmath expression by default. The output parameter can modify the type of the returned value.

If more than one string is specified in the `input` parameter, returns a list of expressions.

Adding new commands

New LaTeX commands can be defined by supplying the `user_defined` parameter. The `user_defined` parameter is a list that contains LaTeX commands as names, and template strings as values. A LaTeX command that matches one of the names is translated into the corresponding string and included in the final plotmath expression. The file `symbols.R` in the source code of this package contains one such table that can be used as a reference.

The template string can include one of the following special template parameters:

- `$arg1`, `$arg2`, ... represent the first, second, ... brace argument. E.g. for `\frac{x}{y}`, `$arg1` is `x` and `$arg2` is `y`.
- `$opt` is an optional argument in square brackets. E.g. for `\sqrt[2]{x}`, `$opt` is `2`.
- `$sub` and `$sup` are arguments in the exponent (^) or subscript (_) following the current expression. E.g. for `\sum^x`, `$sup` is `x`.
- `$LEFT` and `$RIGHT` are substituted the previous and following LaTeX expression relative to the current token.

See the Examples section for an example of using the `user_defined` option.

Examples

```
TeX("$\\alpha$") # plots the greek alpha character
TeX("The ratio of 1 and 2 is $\\frac{1}{2}$")

a <- 1:100
plot(a, a^2, xlab = TeX("$\\alpha$"), ylab = TeX("$\\alpha^2$"))

# create a \\variance command that takes a single argument
TeX("$\\variance{X} = 10$",
  user_defined = list("\\variance" = "sigma[$arg1]^2"))
```

Index

latex2exp, [2](#)
latex2exp_examples, [2](#)
latex2exp_supported, [3](#)

plot.expression, [3](#)
plotmath, [3](#), [5](#)
print.latexexpression, [4](#)
print.latextoken2, [4](#)

render_latex, [5](#)

TeX, [2-4](#), [5](#), [5](#)
text, [3](#)